

# EXS-AQUA67

## Exodus™ AQUA67

WEATHERPROOF IP67 IK10 - WALL ONLY  
MAINTAINED LED EXIT LIGHT



The AQUA67 is a sturdy wall mounted LED Exit Light that is designed to withstand external environments and harsh weather conditions. It produces excellent illumination with a long lasting battery for years of dependable Exit Lighting.

Its robust, water-tight polycarbonate enclosure provides excellent protection against water, dust and impact and is well suited for a range of outdoor applications such as car parks and exposed stairwells, as well as indoor areas such as swimming centres, construction zones and train stations.



### Technical Specifications

Item	Part Number	EXS-AQUA67/A - No Arrow EXS-AQUA67/R - Arrow Right EXS-AQUA67/L - Arrow Left
	Description	LED Weatherproof IP67 IK10 Wall Mount 24m Exit Light c/w Synthium™ Battery
Input	Voltage & Frequency	230VAC ; 50Hz
	Installation	Large terminal block and 20mm <sup>2</sup> cable entry
Output	Light Source	High performance LED bar, 100,000 hours
	Mode of Operation	Maintained
	Power Consumption	2W (standby)
	Emergency Duration	> 120 minutes
Controls	Charger	Intelligent 3-stage charger with Synthium™ battery management system
	Protection	Overcharge, low voltage disconnect, overcurrent, short circuit
	Testing Facility	Manual test switch
	Indicators	Battery charger green LED
Physical	Battery	Synthium™ Lithium Iron Phosphate - 10 year design life
	Diffuser	Screen printed acrylic - pictographs as per part numbers above
	Construction	Flame-retardant polycarbonate
	Mounting	Surface mounted - wall only
	Dimensions L x W x H	385mm x 185mm x 135mm
	IP, IK Rating	IP67, IK10
	Weight	2.5kg
Environment	Operating Temperature	1° to 40°C
	Relative Humidity	0 to 95%
Compliance	Standards	RCM / EMC, AS/NZS 2293, AS/NZS 60598.1
	AS/NZS 2293 Classification	C0 E2.5 C90 E1.6
Accessories	STAR™ Self-Test and Reporting	P/N: EXS-AQUA67/ST
	DALI-compatible	P/N: EXS-AQUA67/DL
	SYNECTIX™ RF Wireless	P/N: EXS-AQUA67/RF
	Replacement Battery	P/N: BAT-AQUA67: Synthium™ LiFePO <sub>4</sub>

NOTE: Product specifications subject to change without prior notice due to ongoing product improvement policy and changes to industry standards.

### Dimensions



### Spacing Table

This product performs the dual role as an 24m Exit Sign and an Emergency luminaire with the following NATA-accredited emergency classifications:

SPACING TABLE		MOUNTING HEIGHT (m)			
NATA Classification		2.1	2.4	2.7	3.0*
EXS-AQUA65	C0 - E2.5	5.4	5.6	5.8	5.8
	C90 - E1.6	4.6	4.7	4.6	0.0

\* Maximum mounting height allowed is 2.7m but for exceptions see AS2293.1:2018



SYNTHIUM™ nanotechnology is an advanced environmentally sustainable energy development that offers extended battery life, low cost of ownership, enhanced performance and improved safety.



SYNECTIX RF



Vision Lighting Supplies Pty Ltd  
10 Pinnacle Pl, Somersby NSW 2250

Vision retains the right to update this data at any time.

P 1300 474 878  
E sales@visionlighting.net  
W www.visionlighting.net