

EXS-PRIME


Exodus™ Prime

ONE BOX SOLUTION

MAINTAINED LED EXIT LIGHT

This low maintenance, wall or ceiling mountable one box solution Exit Sign comes complete with all variations of the Running Man pictogram and offers many years of reliable, succinct and efficient Exit Lighting.

Its no-frills slide and connect style installation mechanism and robust design allows it to be used in a wide variety of indoor applications, ranging from offices through to retail stores, cafes and public spaces in the quickest time possible.




Technical Specifications

Item	Part Number	EXE-LITE	EXS-PRIME
	Description	LED Slide and Connect 24m Exit Light c/w High Temp NiMH Battery	LED Slide and Connect 24m Exit Light c/w Synthium™ Battery
Input	Voltage & Frequency	230VAC : 50Hz	
	Installation	Large terminal block and 20mm² cable entry	
Output	Light Source	High efficacy LED strip, 50,000 hours	
	Mode of Operation	Maintained	
	Power Consumption	3W (standby)	2W (standby)
	Emergency Duration	> 120 minutes	
Controls	Charger	Dual rate boost and trickle charge	Intelligent 3-stage charger with Synthium™ battery management system
	Protection	Overcharge, low voltage disconnect, overcurrent, short circuit	
	Testing Facility	Manual test switch	
	Indicators	Battery charger green LED	
Physical	Diffuser	All variations of Running Man pictogram	
	Construction	Flame-retardant polycarbonate	
	Mounting	Surface mounted - wall or ceiling (single or double side application)	
	Dimensions L x W x H	355mm x 65mm x 210mm	
	IP Rating	IP20	
	Weight	1.5kg	
Environment	Operating Temperature	1° to 40°C	
	Relative Humidity	0 to 95%	
Compliance	Standards	RCM / EMC, AS/NZS 2293, AS/NZS 60598.1	
	AS/NZS 2293 Classification	C0 D2 C90 E1.6	C0 D3.2 C90 E2.5
Accessories	Replacement Battery	P/N: BAT-EXELITE: High temperature NiMH	P/N: BAT-PRIME: Synthium™ LiFePO ₄

NOTE: Product specifications subject to change without prior notice due to ongoing product improvement policy and changes to industry standards.

Dimensions



Spacing Table

This product performs the dual role as an 24m Exit Sign and an Emergency luminaire with the following NATA-accredited emergency classifications:

SPACING TABLE		MOUNTING HEIGHT (m)			
NATA Classification		2.1	2.4	2.7	3.0*
EXE-LITE	C0 - D2	5.2	5.2	5.0	4.8
	C90 - E1.6	4.8	4.8	4.8	4.4
EXS-PRIME	C0 - D3.2	6.5	6.6	6.6	6.5
	C90 - E2.5	5.6	5.8	5.8	6.0

* Maximum mounting height allowed is 2.7m but for exceptions see AS2293.1 2005



SYNTHIUM™ nanotechnology is an advanced environmentally sustainable energy development that offers extended battery life, low cost of ownership, enhanced performance and improved safety.



Vision Lighting Supplies Pty Ltd
10 Pinnacle Pl, Somersby NSW 2250

Vision retains the right to update this data at any time.

P 1300 474 878
E sales@visionlighting.net
W www.visionlighting.net