

ALINYA U60

ALN-U60 - DIRECT/INDIRECT LED EXTRUSION

Elegant & Bespoke



The Alinya range from Vision Lighting enriches a space with clean, unobtrusive illumination. Incorporating a unique reflector and diffuser system the Alinya F60 provides an even light distribution.

Quality internal componentry, ensure a high lifetime for peace of mind and reduced maintenance cost.

Designed for surface mounting, the Alinya U60 is the perfect compliment for education, hospital, and office lighting applications.

PRODUCT SPECIFICATIONS

Wattage:	~26W/m
Lumens:	3800Lm/m
CCT:	3000K 4000K
CRI:	Ra>90
Beam Angle:	Direct/Indirect
Dimming:	DALI Available
Material:	Aluminium Extrusion
Diffuser:	Opal Diffused
Colour:	White Black
Mounting:	Suspended
IP Rating:	IP44
Lifetime:	L80B10>50,000hrs
Pofile Dimensions:	60(W)x80(H)

ALINYA U60

ALN-U60 - DIRECT/INDIRECT LED EXTRUSION

CODING MATRIX

Family		Power		CCT/CRI		Colour		Dimming		Length	
ALNU60	Suspended	-18W	~18W/m	3K9	3000K	BK	Black	(Blank)	Non-Dimmable	(Blank)	per-metre
	Direct/Indirect			4K9	4000K	WT	White	DA	DALI	-1.2m	1200mm

Notes

- Per-metre price for tender/predesign purposes only.
- Lengths available in 300 mm increments; standard lengths as listed.
- Lengths over 3.0 m will be supplied as multiple linkable sections.
- Longer single-section lengths can be supplied on a per-project basis, subject to MOQs.

-1.5m 1500mm
-2.4m 2400mm
-3.0m 3000mm
etc

DIMENSIONAL DIAGRAM

